

(Forts) Gängpressande skruv

	För ST-gängor	
	CSK CSS	KFSK KFSS
Mejseltjocklekx mejselbredd mm		
0,4x2,5 0,5x3 (0,5x4) 0,6x3,5 (0,6x4)	ST 2 —	ST 2.2 —
0,8x4 (0,8x5,5) 1,0x5,5 (1,0x6,5) 1,2x6,5	ST 2.9 ST 3 ST 4.2 ST 4.8	ST 2.9 ST 3.5 ST 4.2 ST 4.8
1,8x8 1,6x8 1,6x10	— — ST 5.5 ST 6.3	— — ST 5.5 ST 6.3
2x12 (2x13) 2,5x14 (2,5x16)	ST 8 ST 9.5	ST 8 ST 9.5

	För ST-gängor	
	RXK RXS	KFX KFXS
(Phillips och Pozidriv/Supadriv)		
0	ST 2.2	ST 2.2
1	ST 2.9	ST 2.9
2	ST 3.5 ST 4.2 ST 4.8	ST 3.5 ST 4.2 ST 4.8
3	ST 5.5 ST 6.3	ST 5.5 ST 6.3
4	ST 8 ST 9.5	ST 8 ST 9.5

Träskruv

	För DIN-skruv			För SMS-skruv		
	TKS	TFS	TKFS	TKS	TFS	TKFS
						
Mejseltjocklekx mejselbredd (SMS 2830) mm	DIN 96	DIN 97	DIN 95	SMS —	SMS 1573	SMS 1574
	Diam. mm		Nr		Diam. mm	Nr
0,5x3 0,8x3,5	2 2.5 2.7		2 3 4		— 2.15	— 2
0,8x4	3 3.5		5 6		2.8	4
1,0x5,5	3.8 4 4.5		7 8 9		3.45	6
1,2x6,5 1,2x8	— — 5 (5.5)		— — 10 (12)		4.15 4.8 5.45 6.15	8 10 12 14
1,6x8 1,6x10 2x12 2,5x14	6 — (7) (10)		14 — (16) (24)		6.8 6.8 7.5 —	16 16 18 —

	För DIN-skruv			För SMS-skruv		
	TKX	TFX	TKFX	TKX	TFX	TKFX
						
För kryss-spår (SMS 2831)	DIN 7996	DIN 7997	DIN 7995	SMS —	SMS —	SMS —
Nr	Diam. mm		Nr		Diam. mm	Nr
0	(2)	(2)			—	—
1	2.5 3	5 5			— 2.8	— 4
2	3.5 4 4.5 5	6 8 9 10			3.45 4.15 4.8 —	6 8 10 —
3	(5.5) 6 (7)	(12) 14 (16)			5.45 6.15 6.8	12 14 16
4	(8)	18			—	—