

Building product declaration

according to BPD associations' standardised format eBVD

2025-03-07 10:20:59

Flexilight PRIMA

1. COMPANY INFORMATION

BMI Sverige AB

Company name:	Organisation number:			
BMI Sverige AB	556013-0709			
Address:	Contact person:			
Pulpetgatan 20	Lars Åhsberg			
E-mail:	Telephone:			
lars.ahsberg@bmigroup.com	070-6045046			
VAT number:	Website:			
	https://bmisverige.se/			
GLN:	DUNS:			
Company was last saved				
2024-12-11 09:55:43				
Company's certification				
ISO 9001 ISO 14001				
Other:				
Bitumentätskiktproduktionen i Malmö är certifierad enligt ISO 9001.				
Ballatan and mildellars				
Policies and guidelines				
The company has a code of conduct/policy/guidelines for dealing with the requirements	n social responsibility in the supplier chain, including procedures for ensuring			
This is third-party audited				
If yes, which if the following guidelines have you affiliated to or management system you have implemented				
UN guiding principles for companies and human rights				
ILO's eight core conventions				
OECD Guidelines for Multinational Enterprises				
✓ UN Global Compact				
ISO 26000				
Other policy guidelines				

Management system

If you have a management system for corporate social responsibility, what out of the following is included in the work?

Mapping	
Risk analysis	
Action plan	
Monitoring	
Sustainability reporting guidelines:	Susta
nligt Årsredovisningslagen (1995:554)	Enlig

2. ARTICLE INFORMATION

Document data

ld:	Version:
C-SE556013070901-91	2
Created:	Last saved:
2025-03-07 09:48:06	2025-03-07 10:20:59
Changes relates to:	
Justering av innehållsdeklarationen.	
Flexilight PRIMA	
Article name:	
Flexilight PRIMA	
Article No/ID concept	
Article identity: GTIN	
7391738009179	

Product group/Product group classification

Product group system	Product group id
BK04	01409

Article description:

Article identity: VAT-ID SE10006458 01-10 006 458

Flexilight underlagsduk används under falsade överläggsplattor (t ex takpannor av betong, tegel eller plåt) på underlag av trä. Duken fungerar som vattenavledande skikt enligt kraven i AMA Hus JSC.61. Klass UD2. Flexilight tillverkas i Sverige för våra specifika byggtraditioner och klimatförhållanden. Underlagsduken är åldringsbeständig och diffusionstät. Stommen är belagd med SBS-modifierad bitumen som gör produkten smidig att hantera även vid låga temperaturer. Under- och översida skyddas av en filt av polypropen.

Flexilight PRIMA kan användas på taklutningar ned till 6° och har liksom PRO 1,20 m breda våder som ger få skarvar och rationell montering. Duken har starka, självhäftande klisterkanter av asfalt i båda sidor och är helt sandfri. Stommen är impregnerad och belagd med asfalt med tillsats av polymer (SBS) som gör produkten smidig att hantera och lägga. Exponeringstid max 2 månader. Ånggenomgångsmotstånd ca Zv 2200x103 s/m eller Sd 58 m.

Declarations of performance:

Declaration of performance number:

Yes

060-1200

Other information:

3. CHEMICAL CONTENT

Chemical content

Does the declaration apply to a product or chemical product?

product

Enter chemical content for the whole article. The concentration is calculated at component level according to the principle of "once an article always an article".

Is there a safety data sheet for the article?

Not applicable

Is there classification of the article?

Not applicable

If yes, indicate the classification of the product under Regulation (EC) No

-

Enter which version of the candidate list has been used (Year, month, day)

2025-01-21

The article is covered by the RoHS Directive:

Enter the weight of the article:

No

Enter how large a proportion of the material content has been declared [% $^{\rm 1}$

100

If 100% material content is not declared, please state the reason

-

If the article contains nanomaterials deliberately added to obtain a particular function, enter these here:

Has the presence of nanomaterials deliberately added to notifiable chemical products been reported to the Product Register

No

Enter the proportion of volatile organic substances [g/litre], applies only to sealants, paints, varnishes and adhesives:

Article and/or sub-components

Phase	Delivery		
Component	Bindemedel	Weight% of product	77 <x<82< th=""></x<82<>

Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
SBS modifierad asfalt		77 <x<84< td=""><td></td><td></td></x<84<>		
SBS modifierad asfalt	Bitumen destillerad	62 <x<65< td=""><td>8052-42-4</td><td></td></x<65<>	8052-42-4	
SBS modifierad asfalt	Bitumen oil (recycled)	9 <x<12< td=""><td>8052-42-4</td><td></td></x<12<>	8052-42-4	
SBS modifierad asfalt	SBS	6 <x<7< td=""><td>91261-65-3</td><td></td></x<7<>	91261-65-3	

Weight% of 1.5 <x<3 product<="" th=""><th></th></x<3>	

Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	Polyeten	1 <x<2< th=""><th>9002-88-4</th><th></th></x<2<>	9002-88-4	
	Polypropen	0.5 <x<1< th=""><th>9003-07-0</th><th></th></x<1<>	9003-07-0	

Component	Stomme		Weight% of product	6 <x<8< th=""></x<8<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
Polyester/glas fiberfilt		6 <x<8< td=""><td></td><td></td></x<8<>		
Polyester/glas fiberfilt	Glasfiber	3 <x<4< td=""><td>65997-17-3</td><td></td></x<4<>	65997-17-3	
Polyester/glas fiberfilt	Polyetylentereftalat	3 <x<4< td=""><td>25038-59-9</td><td></td></x<4<>	25038-59-9	
Component	Ytskikt		Weight% of product	10 <x<12< td=""></x<12<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	PP-filt	10 <x<12< td=""><td>9003-07-0</td><td>•</td></x<12<>	9003-07-0	•
Phase	Mounted			
Component	Bindemedel		Weight% of product	77 <x<82< td=""></x<82<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
SBS modifierad asfalt		77 <x<84< td=""><td></td><td></td></x<84<>		
SBS modifierad asfalt	Bitumen destillerad	62 <x<65< td=""><td>8052-42-4</td><td></td></x<65<>	8052-42-4	
SBS modifierad asfalt	Bitumen oil (recycled)	9 <x<12< td=""><td>8052-42-4</td><td></td></x<12<>	8052-42-4	
SBS modifierad asfalt	SBS	6 <x<7< td=""><td>91261-65-3</td><td></td></x<7<>	91261-65-3	
Component	Stomme		Weight% of product	6 <x<8< td=""></x<8<>
Comment				
Material	Substance	Concentration	EG/CAS/Alternative designation	Other substance properties
		interval (%)	designation	p. 0 p 0. 0.00
Polyester/glas fiberfilt		6 <x<8< td=""><td>designation</td><td>рторогиос</td></x<8<>	designation	рторогиос
Polyester/glas fiberfilt	Glasfiber	• •	65997-17-3	proposition of the control of the co
Polyester/glas fiberfilt	Glasfiber Polyetylentereftalat	6 <x<8< td=""><td>-</td><td></td></x<8<>	-	
		6 <x<8 3<x<4< td=""><td>65997-17-3</td><td>10<x<12< td=""></x<12<></td></x<4<></x<8 	65997-17-3	10 <x<12< td=""></x<12<>
Polyester/glas fiberfilt Polyester/glas fiberfilt	Polyetylentereftalat	6 <x<8 3<x<4< td=""><td>65997-17-3 25038-59-9 Weight% of</td><td></td></x<4<></x<8 	65997-17-3 25038-59-9 Weight% of	
Polyester/glas fiberfilt Polyester/glas fiberfilt Component	Polyetylentereftalat	6 <x<8 3<x<4< td=""><td>65997-17-3 25038-59-9 Weight% of</td><td></td></x<4<></x<8 	65997-17-3 25038-59-9 Weight% of	

Other information:

4. RAW MATERIALS

Is there supporting documentation for the raw materials for third-party certified system for control of origin, raw material extraction, manufacturing or recycling processes or similar (for example BES 6001:2008, EMS certificate, USGBC Program)? If yes, enter system(s):

Raw materials

Total recycled material in the article

•	
Is recycled material included in the article?	
Material	
Bitumenolja recirkulerad	
Share of waste (from own production)	Share of waste (from other people's production)
0	0
Recycled material (treated)	Recycled material
10	0
Weight/percent by weight	
>10 %	
Comment	

Renewable material

Enter	proportion	of	renewable	material	in	the	article
	proportion	O1	TCTTCWabic	material		uic	articic

Included biobased raw material is tested according to ASTM test method D6866:

Crigin of raw material For this product, there has been no withdrawal of virgin fossil material Yes If yes, please indicate the maximum percentage of virgin fossil material that can be included in the material (or item) in question 90 Wood raw materials Wood raw materials are included Included wood raw material is certified How large a proportion is certified [%]? What certification system has been used (for example FSC, CSA, SFI with CoC, PEFC)? Reference number: Enter logging country for the wood raw material and that following criteria have been met. Country of logging: Does not contain type of wood or origin in CITES appendix of endangered species Which version of CITES has been used for the check? The timber has been logged legally and there is certification for this

5. ENVIRONMENTAL IMPACT

Environmental impact during life cycle of the article, production phase module A1-A3 under EN

	, , , , , , , , , , , , , , , , , , ,
Has environmental product declaration been drawn up according t	o EN 15804 or ISO 14025 for the article?
These product-specific rules, known as PCR, have been applied:	Registration number / ID number for EPD:
The International EPD System PCR for Construction Products and CP	S-P-02107
If there is environmental product declaration or other life cycle assessme	nt, describe how the environmental impact of the article is taken into account

from a life cycle perspective:

6. DISTRIBUTION

Distribution of finished article

	Does the supplier apply any system with multiple-use packaging for the article?
	No
	Does the supplier take back packaging for the article?
	No
	Is the supplier affiliated to a system for product responsibility for packaging?
	Yes
	If yes, which packaging and which system?
	Näringslivets Producentansvar (NPA)
	Can packaging/packaging be reused?
	No
	Can packaging/packaging be recycled?
	Yes
	Can packaging/packaging be energy recycled?
	Yes
	Does the supplier use Retursystem Byggpall?
	No
	Other information:
_ (CONSTRUCTION PHASE
	Construction phase
	Does the article make special requirements in storage?
	Yes
	Yes
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products?
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products? No
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products?

8. USE PHASE

Use phase

9.

Does the article make requirements for input materials for operation and maintenance?
No
Specify:
Does the article require supply of energy during operation?
Not applicable
Specify:
Estimated technical service life for the article:
30-40 years
Comment:
Is there energy labelling under the Energy Labelling Directive (2010/30/EU) for the article?
Not applicable
If yes, enter labelling (G to A, A+, A+++, A+++):
If yes, enter marking (G to A)
Other information:
DEMOLITION
Demolition
Is the article prepared for disassembly (dismantling)?
Not applicable
Can the product be separated into pure material types for recycling?
No
Specify:
Does the article require special measures for protection of health and environment in demolition/disassembly?
No
Specify:
Other information:

10. WASTE MANAGEMENT

Delivered article

Is the supplied article covered by the Ordinance (2014:1075) on producer responsibility for electrical and electronic products when it becomes waste?					
No					
Is reuse possible for the whole or parts of the article when it becomes waste?					
No					
Specify:					
Is material recovery possible for the whole or parts of the article when it becomes waste?					
Yes					
Specify:					
Uttjänt/kasserad produkt är möjlig att återvinna genom omarbetning och inblandning i råvara för tillverkning av ny produkt. Detta görs exempelvis i Holland. I vår produktionsanläggning omhändertas sedan 2014 allt produktionsspill och används som råvara för produktion av annan produkt.					
Is energy recovery possible for the whole or parts of the article when it becomes waste?					
Yes					
Specify:					
Uttjänt/kasserad produkt kan energiåtervinnas genom förbränning i godkänd förbränningsanläggning					
Does the supplier have restrictions and recommendation for re-use, material or energy recovery or landfilling?					
No					
Specify:					
Waste code for the delivered article when it becomes waste					
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.					
When the supplied article becomes waste, is it classified as hazardous waste?					
No					
Mounted article					
Is the mounted article classified as hazardous waste?					
No					
Waste code for the mounted article					
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.					

Other information

11. INDOOR ENVIRONMENT

Indoor environment

The article is not intended for indoor use						
The article does not emit any substances						
Emissions from the article not measured						
Does the article have a critical moisture state?						
No						
If yes, state what:						
Noise	Electrical field	Magnetic fields				
Can the article give rise to own noise?	Can the article give rise to electrical fields?	Can the article give rise to magnetic fields?				
Not applicable	Not applicable	Not applicable				
Value:	Value:	Value:				
Unit:	Unit:	Unit:				
Measuring method:	Measuring method:	Measuring method:				
Paints and varnishes						
The article is resistant to fungi and algae in use in wet areas						
Emissions						

The article produces the following emissions in intended use:

Other information