

INSTRUCTIONS FOR USE
PRODUCT SPECIFIC INFORMATION
ONLY ON THIS PAGE

TEGERA® 8830R

Cut resistant glove, winter-lined, nitrile foam, palm-dipped, foam grip pattern, cut resistance level D, acrylic, CRF® Technology, HPPE, polyester, stainless steel fibre yarn, Cat. II, black, blue, withstands contact heat up to 250°C, approved for handling foodstuffs, for allround work

EN ISO 21420:2020 EN 388:2016+A1:2018 4X42D

EN 407:2020 No Flame Protection X2XXXX

EN 511:2006 01X

EN 13739 CUT

EN 13739 ABR



Contact heat rating valid for palm area only

OUTER MATERIAL SPECIFICATION Nitrile
INNER MATERIAL SPECIFICATION Acrylic, HPPE (High performance polyethylene), stainless steel fibre yarn, polyester
SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12
EU-TYPE EXAMINATION (MODULE B) ISSUED BY NOTIFIED BODY: 2777 STA
 Technology Europe Ltd Bractown Business Park, Clonee, Dublin 15, Dublin, Ireland

LATEX FREE YES NO

BRUKSANVISING - KATEGORI II

SE FRAMSIDEN FÖR SPECIFIK PRODUKTINFORMATION

SV

Läs dessa instruktioner noggramt innan du använder produkten.
FÖRKLARING AV SYMBOLER: EN ISO 21420:2020 FÖR ANVÄNDNINGEN EN ISO 21420:2020
X = HAR INTE GENOMGÅTT PROVNING ELLER METODEN INTE LÄMPLIG/RELEVANT FÖR PRODUKTEN
 Varning! Den här produkten har designats för att ge sådant skydd som specificeras i enlighet med EN 2016/425. Kom dock håg att ingen PPE-produkt kan ge fullständig skydd och tillräckligt mätte alltså vid riskfyllda situationer.
EN 407:2020 SKYDDSHANDSAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)
 A: Begärd flampåverkan B: Kontaktvärme C: Korrekttvålning D: Strålningsskydd E: Små stänk av smält metall F: Stora mängder smält metall

EN 388:2016 +A1:2018
 A: Nöttningsmotstånd Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

EN 511:2006
 A: Korrosionsbeständighet Min. 0; Max. 4
 B: Kontaktvärme Min. 0; Max. 4
 C: Vattentätning I (Godkänt)

EN 13739
 A: Skyddsnivå Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

6 PAIRS

Made in China

ONLY FOR EURASIAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
 ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЮ ТР ЦО 19/2011
 «О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»

UK-IMPORTER
 Ejendals Ltd, Sweden House, 5 upper Montagu Street, London, England, W1J 2AG

EJENDALS AB
 Limavägen 28, SE-793 32 Leksand, Sweden
 info@ejendals.com | order@ejendals.com | www.ejendals.com
 Declaration of Conformity → www.ejendals.com/conformity



INSTRUCTIONS FOR USE - CATEGORY II

EN

SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION

Carefully read these instructions before using this product.
DECLARATION OF CONFORMITY
 www.ejendals.com/conformity

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard X= Not submitted to the test or method specified in the glove design or material
Warning! This product is designed to provide protection specified in PPE Regulation (EU) 2016/425 with the detailed levels of performance presented below. However, always remember that no item of PPE can provide full protection and caution must always be taken when exposed to risks.

EN 407:2020 PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)
 A: Limited flame spread B: Contact heat C: Connective heat D: Radiant heat E: Small splashes of molten metal F: Large quantities of molten metal

WARNING (A-F): Min. 0; Max. 4

PROTECTIVE GLOVES AGAINST MECHANICAL RISKS Protection levels 0 = Not tested against the given hazard X= Not submitted to the test or method specified in the glove design or material
Warning! EN 511:2006: If the glove consists of separate parts which are not permanently interconnected, the performance levels and the protection only apply to the complete assembly. If the glove has a performance level of <1, or a knit flampåverkan in EN 407:2020 the glove should not come in contact with molten flame. Glove tested according to the 6.6 "small splashed of molten metal" is not suitable for welding activities. In the event of a molten metal splash the glove may not eliminate all risks of burn and the user shall take the necessary protective measures.
 EN 388:2016 +A1:2018
 A: Abrasion resistance Min. 0; Max. 4
 B: Contact heat Min. 0; Max. 4
 C: Tear resistance Min. 0; Max. 4
 D: Puncture resistance Min. 0; Max. 4
 E: Cut Resistance TDM Min. 0; Max. 4
 F: Impact Protection P=Pass

EN 511:2006
 A: Connective cold Min. 0; Max. 4
 B: Contact cold Min. 0; Max. 4
 C: Water penetration (0 Fail); 1 (Pass)

PROPERTIES: If you wear EN 511:2006 Annex B and C gloves, you must be aware of the following: EN 511:2006 Annex B and C gloves are established certain correlations between these parameters and the level of thermal insulation required to protect in cold conditions. The table given in Annex B of EN 511:2006 is an example of such data.
SUITABLE FOR CONTACT WITH SPECIFIC IN REGULATION (EU) 10/2011 AND 1935/2004
 All gloves/leaves that are suitable for foodstuff may not be suitable for all types of food. To know for which foodstuff the glove/sleeve may be used please see the Food declaration of conformity. Contact Ejendals for more information.

Abrasion resistance according to the American National Standards Institute 105-2016. Levels 1-6
 Cut resistance according to the American National Standard Institute 105-2016. Levels A1-9

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
FINGER DEXTERITY TEST: Min. 1; Max. 5
FITTING AND SIZING: All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. If not explained on the front page, if the shorted model symbols is shown on the front page, the glove is shorter than a standard glove. In order to enhance the contact for special purposes, for example fine assembly work, only wear the glove in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.

STORAGE AND TRANSPORT: Ideally store in dry and dark condition in the original package, between +10° - +30°C.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors, such as storage conditions, usage etc.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
DISPOSAL: According to local environmental legislations. The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

LATEX FREE YES NO

BRUKSANVISING - KATEGORI II

SE FRAMSIDEN FÖR SPECIFIK PRODUKTINFORMATION

SV

Läs dessa instruktioner noggramt innan du använder produkten.
FÖRKLARING AV SYMBOLER: EN ISO 21420:2020 FÖR ANVÄNDNINGEN EN ISO 21420:2020
X = HAR INTE GENOMGÅTT PROVNING ELLER METODEN INTE LÄMPLIG/RELEVANT FÖR PRODUKTEN
 Varning! Den här produkten har designats för att ge sådant skydd som specificeras i enlighet med EN 2016/425. Kom dock håg att ingen PPE-produkt kan ge fullständig skydd och tillräckligt mätte alltså vid riskfyllda situationer.
EN 407:2020 SKYDDSHANDSAR MOT TERMISKA RISKEN (HETTA OCH/ELLER BRAND)
 A: Begärd flampåverkan B: Kontaktvärme C: Korrekttvålning D: Strålningsskydd E: Små stänk av smält metall F: Stora mängder smält metall

EN 388:2016 +A1:2018
 A: Nöttningsmotstånd Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

EN 511:2006
 A: Korrosionsbeständighet Min. 0; Max. 4
 B: Kontaktvärme Min. 0; Max. 4
 C: Vattentätning I (Godkänt)

EN 13739
 A: Skyddsnivå Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt


6 PAIRS

Made in China

ONLY FOR EURASIAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
 ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЮ ТР ЦО 19/2011
 «О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»

UK-IMPORTER
 Ejendals Ltd, Sweden House, 5 upper Montagu Street, London, England, W1J 2AG

EJENDALS AB
 Limavägen 28, SE-793 32 Leksand, Sweden
 info@ejendals.com | order@ejendals.com | www.ejendals.com
 Declaration of Conformity → www.ejendals.com/conformity



INSTRUCTIONS FOR USE - CATEGORY II

EN

SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION

Carefully read these instructions before using this product.
DECLARATION OF CONFORMITY
 www.ejendals.com/conformity

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard X= Not submitted to the test or method specified in the glove design or material
Warning! This product is designed to provide protection specified in PPE Regulation (EU) 2016/425 with the detailed levels of performance presented below. However, always remember that no item of PPE can provide full protection and caution must always be taken when exposed to risks.

EN 407:2020 PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)
 A: Limited flame spread B: Contact heat C: Connective heat D: Radiant heat E: Small splashes of molten metal F: Large quantities of molten metal

WARNING (A-F): Min. 0; Max. 4

PROTECTIVE GLOVES AGAINST MECHANICAL RISKS Protection levels 0 = Not tested against the given hazard X= Not submitted to the test or method specified in the glove design or material
Warning! EN 511:2006: If the glove consists of separate parts which are not permanently interconnected, the performance levels and the protection only apply to the complete assembly. If the glove has a performance level of <1, or a knit flampåverkan in EN 407:2020 the glove should not come in contact with molten flame. Glove tested according to the 6.6 "small splashed of molten metal" is not suitable for welding activities. In the event of a molten metal splash the glove may not eliminate all risks of burn and the user shall take the necessary protective measures.
 EN 388:2016 +A1:2018
 A: Abrasion resistance Min. 0; Max. 4
 B: Contact heat Min. 0; Max. 4
 C: Tear resistance Min. 0; Max. 4
 D: Puncture resistance Min. 0; Max. 4
 E: Cut Resistance TDM Min. 0; Max. 4
 F: Impact Protection P=Pass

EN 511:2006
 A: Connective cold Min. 0; Max. 4
 B: Contact cold Min. 0; Max. 4
 C: Water penetration (0 Fail); 1 (Pass)

PROPERTIES: If you wear EN 511:2006 Annex B and C gloves, you must be aware of the following: EN 511:2006 Annex B and C gloves are established certain correlations between these parameters and the level of thermal insulation required to protect in cold conditions. The table given in Annex B of EN 511:2006 is an example of such data.
SUITABLE FOR CONTACT WITH SPECIFIC IN REGULATION (EU) 10/2011 AND 1935/2004
 All gloves/leaves that are suitable for foodstuff may not be suitable for all types of food. To know for which foodstuff the glove/sleeve may be used please see the Food declaration of conformity. Contact Ejendals for more information.

Abrasion resistance according to the American National Standards Institute 105-2016. Levels 1-6
 Cut resistance according to the American National Standard Institute 105-2016. Levels A1-9

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
FINGER DEXTERITY TEST: Min. 1; Max. 5
FITTING AND SIZING: All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. If not explained on the front page, if the shorted model symbols is shown on the front page, the glove is shorter than a standard glove. In order to enhance the contact for special purposes, for example fine assembly work, only wear the glove in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.

STORAGE AND TRANSPORT: Ideally store in dry and dark condition in the original package, between +10° - +30°C.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors, such as storage conditions, usage etc.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
DISPOSAL: According to local environmental legislations. The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

LATEX FREE YES NO

BRUKSANVISING - KATEGORI II

SE FRAMSIDEN FÖR SPECIFIK PRODUKTINFORMATION

SV

Läs dessa instruktioner noggramt innan du använder produkten.
FÖRKLARING AV SYMBOLER: EN ISO 21420:2020 FÖR ANVÄNDNINGEN EN ISO 21420:2020
X = HAR INTE GENOMGÅTT PROVNING ELLER METODEN INTE LÄMPLIG/RELEVANT FÖR PRODUKTEN
 Varning! Den här produkten har designats för att ge sådant skydd som specificeras i enlighet med EN 2016/425. Kom dock håg att ingen PPE-produkt kan ge fullständig skydd och tillräckligt mätte alltså vid riskfyllda situationer.
EN 407:2020 SKYDDSHANDSAR MOT TERMISKA RISKEN (HITZE UND/ODER FEUER)
 A: Begärd flampåverkan B: Kontaktvärme C: Korrekttvålning D: Strålningsskydd E: Små stänk av smält metall F: Stora mängder smält metall

EN 388:2016 +A1:2018
 A: Nöttningsmotstånd Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

EN 511:2006
 A: Korrosionsbeständighet Min. 0; Max. 4
 B: Kontaktvärme Min. 0; Max. 4
 C: Vattentätning I (Godkänt)

EN 13739
 A: Skyddsnivå Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

6 PAIRS

Made in China

ONLY FOR EURASIAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
 ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЮ ТР ЦО 19/2011
 «О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»

UK-IMPORTER
 Ejendals Ltd, Sweden House, 5 upper Montagu Street, London, England, W1J 2AG

EJENDALS AB
 Limavägen 28, SE-793 32 Leksand, Sweden
 info@ejendals.com | order@ejendals.com | www.ejendals.com
 Declaration of Conformity → www.ejendals.com/conformity



INSTRUCTIONS FOR USE - CATEGORY II

EN

SEE FRONT PAGE FOR PRODUCT SPECIFIC INFORMATION

Carefully read these instructions before using this product.
DECLARATION OF CONFORMITY
 www.ejendals.com/conformity

EXPLANATION OF PICTOGRAMS 0 = Below the minimum performance level for the given individual hazard X= Not submitted to the test or method specified in the glove design or material
Warning! This product is designed to provide protection specified in PPE Regulation (EU) 2016/425 with the detailed levels of performance presented below. However, always remember that no item of PPE can provide full protection and caution must always be taken when exposed to risks.

EN 407:2020 PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)
 A: Limited flame spread B: Contact heat C: Connective heat D: Radiant heat E: Small splashes of molten metal F: Large quantities of molten metal

WARNING (A-F): Min. 0; Max. 4

PROTECTIVE GLOVES AGAINST MECHANICAL RISKS Protection levels 0 = Not tested against the given hazard X= Not submitted to the test or method specified in the glove design or material
Warning! EN 511:2006: If the glove consists of separate parts which are not permanently interconnected, the performance levels and the protection only apply to the complete assembly. If the glove has a performance level of <1, or a knit flampåverkan in EN 407:2020 the glove should not come in contact with molten flame. Glove tested according to the 6.6 "small splashed of molten metal" is not suitable for welding activities. In the event of a molten metal splash the glove may not eliminate all risks of burn and the user shall take the necessary protective measures.
 EN 388:2016 +A1:2018
 A: Abrasion resistance Min. 0; Max. 4
 B: Contact heat Min. 0; Max. 4
 C: Tear resistance Min. 0; Max. 4
 D: Puncture resistance Min. 0; Max. 4
 E: Cut Resistance TDM Min. 0; Max. 4
 F: Impact Protection P=Pass

EN 511:2006
 A: Connective cold Min. 0; Max. 4
 B: Contact cold Min. 0; Max. 4
 C: Water penetration (0 Fail); 1 (Pass)

PROPERTIES: If you wear EN 511:2006 Annex B and C gloves, you must be aware of the following: EN 511:2006 Annex B and C gloves are established certain correlations between these parameters and the level of thermal insulation required to protect in cold conditions. The table given in Annex B of EN 511:2006 is an example of such data.
SUITABLE FOR CONTACT WITH SPECIFIC IN REGULATION (EU) 10/2011 AND 1935/2004
 All gloves/leaves that are suitable for foodstuff may not be suitable for all types of food. To know for which foodstuff the glove/sleeve may be used please see the Food declaration of conformity. Contact Ejendals for more information.

Abrasion resistance according to the American National Standards Institute 105-2016. Levels 1-6
 Cut resistance according to the American National Standard Institute 105-2016. Levels A1-9

EN ISO 21420:2020 PROTECTIVE GLOVES - GENERAL REQUIREMENTS AND TEST METHODS
FINGER DEXTERITY TEST: Min. 1; Max. 5
FITTING AND SIZING: All sizes comply with the EN ISO 21420:2020 for comfort, fit and dexterity. If not explained on the front page, if the shorted model symbols is shown on the front page, the glove is shorter than a standard glove. In order to enhance the contact for special purposes, for example fine assembly work, only wear the glove in a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimal level of protection.

STORAGE AND TRANSPORT: Ideally store in dry and dark condition in the original package, between +10° - +30°C.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
SHELF LIFE: The nature of the materials used in this product means that the life of this product cannot be determined as it will be affected by many factors, such as storage conditions, usage etc.
CARE AND MAINTENANCE: Gloves should be cleaned completely before use. Inspect the gloves for any defects or imperfections and avoid wearing damaged gloves. Ensure the gloves fit well, when removing your gloves, hold the outside edge of the glove and peel the glove away and hold it in a closed hand. Use unpowdered finger and slide to peel the remaining glove off from the inside. Do not use hazardous tools. Tearing and shredding may occur. Do not use gloves for purposes other than intended.
DISPOSAL: According to local environmental legislations. The glove contains natural rubber which may cause allergy.
ALLERGENS: This product may contain components that may be a potential risk to allergic reactions. Do not use in case of hypersensitivity signs. For more information contact Ejendals.

LATEX FREE YES NO

BRUKSANVISING - KATEGORI II

SE FRAMSIDEN FÖR SPECIFIK PRODUKTINFORMATION

SV

Läs dessa instruktioner noggramt innan du använder produkten.
FÖRKLARING AV SYMBOLER: EN ISO 21420:2020 FÖR ANVÄNDNINGEN EN ISO 21420:2020
X = HAR INTE GENOMGÅTT PROVNING ELLER METODEN INTE LÄMPLIG/RELEVANT FÖR PRODUKTEN
 Varning! Den här produkten har designats för att ge sådant skydd som specificeras i enlighet med EN 2016/425. Kom dock håg att ingen PPE-produkt kan ge fullständig skydd och tillräckligt mätte alltså vid riskfyllda situationer.
EN 407:2020 SKYDDSHANDSAR MOT TERMISKA RISKEN (HITZE UND/ODER FEUER)
 A: Begärd flampåverkan B: Kontaktvärme C: Korrekttvålning D: Strålningsskydd E: Små stänk av smält metall F: Stora mängder smält metall

EN 388:2016 +A1:2018
 A: Nöttningsmotstånd Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

EN 511:2006
 A: Korrosionsbeständighet Min. 0; Max. 4
 B: Kontaktvärme Min. 0; Max. 4
 C: Vattentätning I (Godkänt)

EN 13739
 A: Skyddsnivå Min. 0; Max. 4
 B: Skärsmått Min. 0; Max. 5
 C: Rivkraft Min. 0; Max. 5
 D: Punkteringsmotstånd Min. 0; Max. 4
 E: Slit Min. 0; Max. 4
 F: Stöt/dämpning P=Godkänt

6 PAIRS

Made in China

ONLY FOR EURASIAN ECONOMIC COMMUNITY CUSTOMS UNION MEMBERS
 ПРОДУКЦИЯ СООТВЕТСТВУЕТ ТРЕБОВАНИЮ ТР ЦО 19/2011
 «О БЕЗОПАСНОСТИ СРЕДСТВ ИНДИВИДУАЛЬНОЙ ЗАЩИТЫ»

UK-IMPORTER
 Ejendals Ltd, Sweden House, 5 upper Montagu Street, London, England, W1J 2AG

EJENDALS AB
 Limavägen 28, SE-793 32 Leksand, Sweden
 info@ejendals.com | order@ejendals.com | www.ejendals.com
 Declaration of Conformity → www.ejendals.com/conformity



